

SUPAPORE TP

AMAZON

PLEATED MEMBRANE FILTER CARTRIDGE



SUPAPORE TP Microfiltration cartridges have been designed specifically for use in a wide range of aggressive gas and liquid processing applications. Its naturally hydrophobic PTFE membrane makes this cartridge an ideal choice for systems requiring excellent compatibility, reliability and a consistently high quality filtrate.

Product Features

SUPAPORE TP cartridges feature:

- A naturally hydrophobic PTFE membrane rated at 0.2µm in liquids and 0.01µm in gases
- Polypropylene support
- Minimal fibre migration
- Wide chemical compatibility
- Validation by bacterial and aerosolised bacteriophage challenge

All cartridges are thermally bonded and adhesive free. Each unit is pre-flushed with ultra-pure water and integrity tested before final assembly*1.

- Can be steam sterilised
- Sanitisable
- Meet current US FDA CFR Title 21 requirements
- Fully integrity testable by Water Intrusion, Bubble Point or Diffusion Flow test*1
- All B grade modules are integrity tested during manufacture

Available in a wide range of grades & absolute rated pore sizes:

- 0.1, 0.2, 0.45, 1.0µm and solvent grade
- General Grade
- Biological Grade

Suitable for most sanitisation regimes including steaming, autoclaving, hot-water flush and most common sanitising agents.

(Note: Steaming, autoclaving and hot water sanitisation must use the glass filled end-cap option)

Amazon Filters manufactures a comprehensive range of filter housings for **SUPAPORE TP** cartridges including the industrial **50** and **60 Series** and **the 70 Series** for hygienic applications. Please consult our Sales Office for further details on the full range.



SUPAPORE TP FEATURES AND BENEFITS

- Fully Integrity Testable - Water Intrusion, Bubble Point and Diffusional Flow values provided for all biological grade pore sizes*1
- Validated*2 removal ratings for consistent and reliable performance
- Feature naturally hydrophobic PTFE membrane and polypropylene hardware
- Thermal bonding process eliminates adhesives and ensures minimal extractables
- Identification mark on every cartridge
- Full product guide available

*1 B grade only

*2 See product guides for further details stating test method and rated efficiencies

SUPAPORE TP

TECHNICAL DATA

Dimensions

Outside Diameter: 70mm
 Typical Surface Area: 0.73-0.80m² (Per 10")
 Length: See ordering guide

Sterilisation and Sanitisation*³

Steam or Autoclave: 136°C for 30 mins (100 cycles)
 Hot Water: 90°C for 30 mins (0.2 bar Δp max)

*³Applies to single open end cartridges only. For all steaming and hot water applications, the Glass Filled end cap option must be used.

Maximum Operating Conditions

Temperature: 80°C

Recommended Maximum Differential Pressure:

Forward Flow: 5.0 bar @ 20°C
 Reverse Flow: 2.1 bar @ 20°C

Product validation guide available on request. All SUPAPORE TP cartridges are manufactured under strict control with batch number identification, giving full traceability on all components.



Materials of Construction

Filter Media: PTFE
 Media Support: Polypropylene (PP)
 Cage, Core & End Caps: Polypropylene (PP)

Integrity Test Specification

B Grade

Micron Rating	Bubble Point In 60/40 IPA/Water	Diffusion Flow (cc/min/10") In 60/40 IPA/Water
0.10µm	≥ 1620mbar (23.5 psi)	≤ 10 @ 1000mbar
0.22µm	≥ 1080mbar (15.7 psi)	≤ 10 @ 800mbar
0.45µm	≥ 630mbar (9.1 psi)	≤ 10 @ 400mbar



INDUSTRIES AND APPLICATIONS

- Food and Beverage** • CO₂ lines, Sterile vent for storage and transfer tanks
- Pharmaceutical** • Solvent filtration, polishing
- Fine Chemicals** • Polymers, Aggressive acids, Bases, Solvents, Ozonated DI Water
- Electronics** • Photoresists, Acids, Etch Solutions

AMAZON FILTERS LTD.

ALBANY PARK ESTATE, FRIMLEY ROAD,
 CAMBERLEY, SURREY, GU16 7PG
 ENGLAND

Tel: +44 (0) 1276 670 600

Fax: +44 (0) 1276 670 101

Email: sales@amazonfilters.co.uk

Web: www.amazonfilters.com



Certificate No. FM39584

Distributed by: