

66 SERIES HFC

High Flow Liquid and Gas Housing




The **66 Series HFC** housing range is specifically designed for use with the large bore **SupaPleat HFC** and **SupaSpun HFC** cartridges to provide a filtration system that offers maximum efficiency, high flow rates and long life. This high quality electropolished 316L stainless steel housing is easy to use and is suited to many filtration processes across a range of industries.




Available in a selection of sizes and with a choice of connections and closure types the optimum housing can be provided for each application.

The **66 Series HFC** housing is available to be used with 20", 40" or 60" cartridges. It can be installed in either the vertical or horizontal position and can be supplied with fixed or adjustable legs. This ensures that the housing can normally be used even where space or changes to inlet and outlet pipework are limited.

Product Features

- Designed for high flow systems
- Multi cartridge units available up to 30 round
- Easy and quick cartridge change-out
- Electropolished inside and out
- Available for 20", 40" or 60" filters
- Each housing is hydrostatically pressure tested
- Available with 3" or 4" connections and in a range of types
- Can be supplied with adjustable or fixed legs where required
- Rated at 10 bar g liquid, 3 bar g gas
- PED and ATEX Compliant



Accessories	
Pressure Gauge and Vent Valve Kit	
Pressure Gauge and Auto Vent Valve Kit	
Ball Valve and Nipple	

Features and Benefits

- Designed for use with the **SupaPleat HFC** and **SupaSpun HFC** cartridges for maximum flow rates
- Utilises large bore cartridge allowing quick and easy filter change out
- Can be used vertically or horizontally with or without legs
- Flexible design allows use of either V band or Rathmann clamp closure
- Full housing customisation service available

Product Range

Amazon Filters design and manufacture an extensive range of liquid filtration systems, providing one of the widest selections of filtration vessels, depth filters and pleated cartridges available today, ensuring excellent process and filter compatibility. As one of Europe's leading manufacturers of filtration systems, Amazon Filters is able to offer a solution to meet all filtration requirements. Amazons' filters are manufactured in clean room conditions and all products come with detailed Product Validation Guides and Technical Support documentation.



AMAZON

66 Series HFC Technical Data

Maximum Operating Conditions

Pressure Range: Liquid: Vee clamp: 10 bar g
Bolted: FV / 10 bar g
Gas: Vee clamp: 3 bar g
Bolted: FV / 3 bar g
Temperature Range: -10°C / 150°C

Materials of Construction

Body: 316L St. Steel
Closure: Vee Clamp - 304 St. Steel
Bolts - Zinc plated carbon steel
(Optional stainless steel)

Finish

Vessel: Electropolished

Connections

Inlet/Outlet: 3" Flanged
Vent: Horizontal: ½" BSPM
Vertical: ¼" BSP
Drains: ½" BSPM

Model	Dimensions					Volume (Litres)	Dry Weight (kg)
	A	B	C	D	E		
66012CAC30C1EE	988	791	181	201	500	27.4	31.0
66014CAC30C1EE	1499	1302	181	201	1000	43.5	38.4
66014CAI30C1EE	1499	1302	181	201	1000	43.5	42.0
66016CAI30C1EE	2007	1810	181	201	1500	56.4	49.6

PED*/PESR** Status:

Fluid Groups: Compliant with PED 2014/68/EU and PESR 2016 No. 1105
Liquids Group 1 + 2
Gas Group 2
Marking: CE
Exceptions: Group 1 liquids - Explosive

ATEX:

Compliant with 2014/34/EU and
Explosive Atmosphere Regulations 2016
II 2G Ex h IIC T150 Gb
II 2D Ex h IIIC T150 Db

* Pressure Equipment Directive

** Pressure Equipment (Safety) Regulations No. 1105

Ordering Guide

Technical drawings for each individual housing showing dimensions, volume, heights, maximum temperatures and design pressures available on request.

6601	4	C	A	I	30	C	1	E	E
No of Stacks	Cartridge Length	Cartridge End Cap Style	Closure Style	Mounting	Connection	Connection Type	Materials	Finish	Seal
6601 - 1 (Available up to 30 round please contact the Sales Office)	2 - 20" 4 - 40" 6 - 60"	C - HFC Cartridge	A - Cast Vee Clamp H - Hinged Plus Bolts W - Hinged + St. St Bolts	I - Adjustable Legs - Horizontal (40" and 60" only) C - Adjustable Legs - Vertical (20" and 40" only)	20 - 2" 30 - 3" 40 - 4"	A - BSPM C - EN1092-1 Flange PN16 G - Table 'E' Flange H - ASME Flange 150# K - Stub Pipe L - BS4825-3 Tri Clamp M - DIN11851 N - RJTM P - SMS M (Swedish) R - IDFM S - DIN2633 Flange	1 - 316 st.st (L Grade)	E - Electropolished	E - EPDM F - FEP / Silicone (Flat cover only) S - Silicone V - Viton

Example: 66014CAI30C1EE= 66 Series, 1 x 40" HFC cartridge, Cast vee clamp closure, Adjustable legs - Horizontal, 3" EN1092-1 Flange PN16 connections. 316L St. Steel construction with EPDM gaskets, electropolished all over.

AMAZON FILTERS LTD.

Albany Park Estate, Camberley, Surrey, GU16 7PG, ENGLAND

Tel: +44 (0) 1276 670 600 Email: sales@amazonfilters.co.uk Web: www.amazonfilters.com